



NEO LACQUER THINNER 300

PRODUCT CODE: LT00

TECHNICAL DATA SHEET NO. 07-Solvents & Thinners

NOVEMBER 2018

NEO Lacquer Thinner 300 has a slightly slower evaporation rate than NEO Special Thinner and results in a better flow out of a wood lacquer.

Use NEO Lacquer Thinner 300 as Thinner for:	<ul style="list-style-type: none">• NEO NC Lacquer (nc00)• NEO Sanding Sealer (ss00)
Product Base	A blend of aromatic hydrocarbon solvents, esters, ketones and alcohol.
Quantities	<ul style="list-style-type: none">• Available in 1 litre, 5 litres, 20 litres and 200 litres.• NEO Lacquer Thinner 300 is not packed in plastic containers in order to avoid possible ignition by static electricity.
Precautions	<ul style="list-style-type: none">• NEO Lacquer Thinner 300 is a flammable liquid.• Never store in direct sunlight.• Store in a dry and cool place.• Familiarize yourself with your municipal and insurers regulations regarding storage of flammable liquids.• Avoid the inhalation of solvent vapours, which might lead to dizziness and even drowsiness.• Constant exposure to solvent vapours in high concentration can be detrimental to your health.• Never use NEO Lacquer Thinner 300 to wash or clean your hands or any part of the skin as it may cause skin irritation.
Disclaimer	NEO Paints can not be held liable if the product fails due to improper usage.
NEO PAINTS FACTORY (PTY) LTD Reg No 2002/214	
12 Bell Street, Southern Industrial Area PO Box 5005 Windhoek, NAMIBIA Tel. +(264) 61-384 700 – Fax +(264) 61-233 914	Hanna Mupatani Road PO Box 762 Walvis Bay, NAMIBIA Tel. +(264) 64-204 026 – Fax +(264) 64-204 010