



NEO MINERAL TURPENTINE

PRODUCT CODE: MT00

TECHNICAL DATA SHEET NO. 07-Solvents & Thinners

NOVEMBER 2018

Use NEO Mineral Turpentine as a Thinner for:	<ul style="list-style-type: none">• NEO Dur Eggshell (SABS 515-2) (sg00)• NEO Dur High Gloss (SABS 630-2) (hg00)• NEO Silk (ns00)• NEO Universal Undercoat (wu00)• NEO Pink Primer (pi00)• NEO Window Primer (wp10)• NEO Plastic Varnish (pv00)• NEO Copal Varnish (iv00)• NEO Stain Varnish (sv10)• NEO Siegelack (sl00)• NEO Woodcoating (wc00)• NEO Linseed Oil (lo00)• NEO Floor Paint (fp00)
Product Base	Aliphatic Hydrocarbon solvent with low toxicity.
Quantities	<ul style="list-style-type: none">• Available in 1 litre, 5 litres, 20 litres and 200 litres.• NEO Mineral Turpentine is not packed in plastic containers in order to avoid possible ignition by static electricity.
Precautions	<ul style="list-style-type: none">• NEO Mineral Turpentine is a flammable liquid.• Never store in direct sunlight.• Store in a dry and cool place.• Familiarize yourself with your municipal and insurers regulations regarding storage of flammable liquids.• Avoid the inhalation of solvent vapours, which might lead to dizziness and even drowsiness.• Constant exposure to solvent vapours in high concentration can be detrimental to your health.• Never use NEO Mineral Turpentine to wash or clean your hands or any part of the skin as it may cause skin irritation.
Disclaimer	NEO Paints can not be held liable if the product fails due to improper usage.
NEO PAINTS FACTORY (PTY) LTD Reg No 2002/214	
12 Bell Street, Southern Industrial Area PO Box 5005 Windhoek, NAMIBIA Tel. +(264) 61-384 700 – Fax +(264) 61-233 914	Hanna Mupatani Road PO Box 762 Walvis Bay, NAMIBIA Tel. +(264) 64-204 026 – Fax +(264) 64-204 010