

NEO PAINT REMOVER

PRODUCT CODE: PR00

TECHNICAL DATA SHEET NO. 04-Repair & Renovation NOVEMBER 2018

Product Decoration			
Product Description	A classic, highly effective, methylene chloride based paint remover.		
Application Areas	Interior and exterior use.		
	Previously painted areas where the coating has to be removed.		
	NEO Paint Remover is a highly effective paint remover for use on enamel The paint remover for use on the paint remover for use on enamel The paint remover for use of th		
	paints, varnishes and other coatings. The paint remover lifts off several coating		
	layers of paint at a time.		
	NEO Paint Remover will have limited or no effect on PVA emulsion paints, two		
	component coatings and chemical resistant finishes.		
Product Features	 Highly effective against a range of paint and varnish types - removes several layers at once. 		
	NEO Paint Remover is a quick working paint remover, which lifts off existing old		
	paint coatings from the substrate within minutes.		
	NEO Paint Remover is a paste, which can be applied on vertical surfaces as well.		
	About 10 to 20 minutes after application, the old paint varnish coatings will come		
	loose and form bubbles. With the use of a paint scraper the old paint as well as		
	remaining paint remover can be removed.		
	Should there be many layers of old paint, this process might have to be repeated.		
	It is very important to remove all traces of paint remover by means of rinsing well with warm water and seen before applying new paint.		
	with warm water and soap before applying new paint.		
	Easy to use. Note the second like the se		
	Non flammable.		
Droduct Date	Washes off with water. Action Time		
Product Data	Spreading Rate 2-3 square metres per litre		
Application Dataila	2-3 Square metres per litre		
Application Details	Devok application		
 Application Method 	Brush application.		
• Cleaning	Never apply NEO Paint Remover by spraying. Water and soap (dishwashing liquid).		
B 1			
• Application			
	Brush a <i>generous / thick</i> coat of NEO Paint Remover on to the area that needs stripping in small manageable sections (lightly sand if the paint is your old or well.)		
	stripping in small manageable sections (lightly sand if the paint is very old or well cured to aid penetration).		
	 Allow the material to stay in contact for 10 to 20 minutes until the paint starts 		
	bubbling and lifting.		
	Remove with a paint scraper.		
	For very thick or very old, cured coatings, apply a second generous application		
	and repeat the waiting and scraping process.		
	Wash off/rinse all traces of NEO Paint Remover with copious amounts of warm		
	water/soap.		
	Allow to dry well before applying new paint.		
	Clean up application equipment and accidental spillage/stain with clean tap		
	water/dishwashing liquids.		
	When applying, wear gloves and goggles and avoid skin contact. If skin contact		
	occurs, wash off with copious amounts of clean water/soap.Avoid the vapours - only use in well ventilated areas.		
	By brush application only.		
	Never apply NEO Paint Remover by spraying.		
Surface Preparation			
 Previously Painted 	Apply a generous/thick coat of NEO Paint Remover on to the existing paint		
Surfaces	coating.		
	Allow to react for 10 to 20 minutes. Then remove loose paint coatings and		
	remaining paint remover with a paint scraper.		
	Rinse well with warm water and soap (dishwashing liquid) to remove all traces of		
	paint remover.		
	Repeat if required.		
	Wooden substrates might require sanding before the application of new		
	paint/varnish coatings.		



NEO PAINT REMOVER

PRODUCT CODE: PR00

TECHNICAL DATA SHEET NO. 04-Repair & Renovation NOVEMBER 2018

Colour Range and Quantities	 Semi-transparent, thick paste. Available in 500ml,1 litre and 5 litres (20 litres on request only). 		
Precautions	 NEO Paint Remover is not flammable. Avoid skin contact - wear rubber gloves for protection. Ventilate well - avoid inhaling vapours. Remove any stains immediately with warm water and soap. 		
Disclaimer	NEO Paints can not be held liable if the product fails due to improper surface preparation or application.		
NEO PAINTS FACTORY (PTY) LTD			
Reg No 2002/214			
12 Bell Street, Southern Industrial Area		Hanna Mupatani Road	
PO Box 5005		PO Box 762	
Windhoek, NAMIBIA		Walvis Bay, NAMIBIA	
Tel. +(264) 61-384 700 - Fax +(264) 61-233 914		Tel. +(264) 64-204 026 - Fax +(264) 64-204 010	