



NEO REIBEPUTZ

TEXTURED COATING

PRODUCT CODE: RP00

TECHNICAL DATA SHEET NO. 01-Wall Paints

NOVEMBER 2018

Product Description	New generation water based, interior / exterior, long-life, structured scratch plaster type coating containing distinct scratch marks. Scratch plaster is a thick coat plaster.	
Application Areas	<ul style="list-style-type: none">• Interior and exterior use.• Long-life exterior protection of buildings.• Used as a feature on interior walls.• New or weathered cement tiles.• New or weathered fibre cement sheeting.• New or weathered plaster.• Previously painted substrates.• Primed metal and wooden substrates.	
Product Features	<ul style="list-style-type: none">• Highly durable and UV resistant.• Forms a hard, solid, nearly indestructible coating for interior and exterior plastered walls.• Distinct scratch marks provide an attractive appearance.• Scratch plaster effect to hide surface imperfections.• Water resistant.• Excellent adhesion.• Quick drying.• Low odour.• One coat of NEO Reibeputz is required for best results. But the applicator must be an experienced plasterer or poor results will be achieved.• If correctly applied to a properly prepared substrate, the product has a life expectancy of 7-10 years, possibly longer.	
Product Data	Resin Base	Acrylic emulsion with marble and quartz aggregates
	Drying Time	Touch dry: ± 60 minutes Hard dry: 3-4 hours
	Film Thickness	Depends on aggregate thickness
	Spreading Rate	Fine (1.6mm) = ± 2,2 liter per square metre Medium (3.2mm) = ± 2,5 liter per square metre Coarse (4.8mm) = ± 3,2 liter per square metre
	Surface Appearance	Scratch plaster type coating containing distinct scratch marks.
Application Details		
• Mixing	Always stir well before use with a flat paddle.	
• Application Method	With trowel only by an experienced plasterer.	
• Thinning	Under no circumstances may the product be diluted.	
• Cleaning	Water.	
• Application	<ul style="list-style-type: none">• Stir well before use.• To be applied by trowel only.• NEO Reibeputz may under no circumstances be diluted.• One coat of NEO Reibeputz is required for best results. But the applicator must be an experienced plasterer or poor results will be achieved.• NEO Reibeputz must be applied with strokes in the same direction otherwise an irregular pattern will be achieved.• Allow to dry over night before recoating.• During application it is quite possible that some scratch marks penetrate the coating right to the substrate and the substrate may become visible. For this reason we recommend to prime the plaster with a coat of NEO Dur (ep00) tinted in the same shade as the successive coat of NEO Reibeputz.• Clean up application equipment with clean tap water.• If required, NEO Reibeputz can be overcoated with NEO Dur (ep00) in a wide range of shades to give added protection.• Do not apply before 09:00 and after 16:00 in the winter.• Do not apply exterior if it looks like rain will occur within 4-6 hours of application.	
Surface Preparation		
• Mild Steel	Clean affected areas back to bright metal.	



NEO REIBEPUTZ

TEXTURED COATING

PRODUCT CODE: RP00

TECHNICAL DATA SHEET NO. 01-Wall Paints

NOVEMBER 2018

(Renovation)	<ul style="list-style-type: none">• Spot prime with NEO Corroguard (cg00).• Apply one coat of NEO Reibeputz.• NEO Reibeputz must be applied with strokes in the same direction otherwise an irregular pattern will be achieved.
<ul style="list-style-type: none">• Mild Steel (New)	<ul style="list-style-type: none">• Degrease surfaces with NEO Metal Conditioner (mc00) to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free.• After drying, the whole substrate is coated with NEO Corroguard (cg00).• Apply one coat of NEO Reibeputz with a trowel.• NEO Reibeputz must be applied with strokes in the same direction otherwise an irregular pattern will be achieved.
<ul style="list-style-type: none">• Dry, Uncoated Concrete Surfaces• Fibre Cement Surfaces (Uncoated, Weathered or New)• Raw Plaster• Precast	<ul style="list-style-type: none">• Make sure surface is dry and firm.• Remove all dust, foreign material, fungal and algae growth.• On areas where moisture ingress can be expected (top of parapet walls, whole surfaces of garden / boundary / retention walls) apply one generous coat of NEO Salt Stop (ss30).• Prime with NEO Contractors Premium Primer (apc00).• Repair any cracks, holes and blemishes with NEO Aurora Filler (ef00) or NEO Repair Paste (nrp07).• Apply one coat of NEO Bonding Liquid (ig00) to cover NEO Aurora Filler (ef00) or NEO Repair Paste (nrp07).• Sand well and remove dust.• Apply one coat of NEO Reibeputz with a trowel.• NEO Reibeputz must be applied with strokes in the same direction otherwise an irregular pattern will be achieved.
<ul style="list-style-type: none">• Previously Painted Surfaces• Precast	<ul style="list-style-type: none">• We do not recommend the application of NEO Reibeputz on previously painted surfaces, because the old coating may loose adhesion and will accordingly not be able to carry the coating of NEO Reibeputz.• Make sure old paint coatings are firm and solid.• Check the adhesion of the substrate.• Remove all loose, flaking and bubbling paint.• Remove all dust, grease, foreign material, fungal and algae growth.• If friable or powdery, seal with NEO Bonding Liquid (ig00).• Apply one coat of NEO Reibeputz with a trowel.• NEO Reibeputz must be applied with strokes in the same direction otherwise an irregular pattern will be achieved.
Colour Range and Quantities	<ul style="list-style-type: none">• NEO Reibeputz is available in white as well in a limited range of shades in minimum batch quantities of 200 liters.• Available in 20 litres.
Precautions	<ul style="list-style-type: none">• NEO Reibeputz is not flammable.• Contains no toxic substances.
Disclaimer	NEO Paints can not be held liable if the product fails due to improper surface preparation or application.
NEO PAINTS FACTORY (PTY) LTD Reg No 2002/214	
12 Bell Street, Southern Industrial Area PO Box 5005 Windhoek, NAMIBIA Tel. +(264) 61-384 700 – Fax +(264) 61-233 914	Hanna Mupatani Road PO Box 762 Walvis Bay, NAMIBIA Tel. +(264) 64-204 026 – Fax +(264) 64-204 010