



NEO GLUE

FOR WOOD

PRODUCT CODE: NG00

TECHNICAL DATA SHEET NO. 04-Repair & Renovation

NOVEMBER 2018

Product Description	NEO Glue is a high quality wood glue made from a pure PVA emulsion. It contains no fillers.	
Application Areas	<ul style="list-style-type: none">• Interior and exterior use.• NEO Glue can be used for all types of woodwork.• Suitable for use with all types of solid wood as well as most man-made fiber boards as well as paper.	
Product Features	<ul style="list-style-type: none">• NEO Glue can be used for all types of woodwork. The glue dries quickly to a solid, hard and indestructible bond between the wooden components.• NEO Glue is a universal product and suitable for some accelerated hardening methods.• NEO Glue is based on a polyvinyl acetate emulsion and is a general-purpose type of wood glue.• The glue dries to a firm bond within 30-60 minutes depending on temperature and moisture.• NEO Glue is reasonably water resistant but should not be used for boat construction.• NEO Glue should never be applied if temperatures are below +5 degrees Celsius and not on cold winter mornings.• For use with melamine sheeting and other synthetic materials, consult the NEO Paints technical department for advice.	
Product Data	Resin Base	Polyvinyl acetate emulsion
	Drying Time	30-60 minutes depending on temperature and moisture
Application Details		
<ul style="list-style-type: none">• Application Method	Hand or machine application.	
<ul style="list-style-type: none">• Cleaning	Water.	
<ul style="list-style-type: none">• Application	<ul style="list-style-type: none">• NEO Glue is suitable for hand or machine application.• Once dry, NEO Glue is insoluble by water.	
Surface Preparation		
<ul style="list-style-type: none">• Wood and Fibre board	<ul style="list-style-type: none">• The surface must be completely dry.• Remove any fatty, greasy substances and dust from substrate.• Apply NEO Glue on both objects/surfaces to be bonded together.• Apply a moderate force with a vice or clamp for 45 minutes.	
Colour Range and Quantities	<ul style="list-style-type: none">• NEO Glue is a white liquid that dries to a clear, transparent film.• Available in the following sizes:<ul style="list-style-type: none">○ 500 ml plastic bottles with spout○ 5 litre plastic bottles○ 20 litre plastic buckets○ 200 litre drums on request	
Precautions	NEO Glue contains no harmful substances.	
Disclaimer	NEO Paints can not be held liable if the product fails due to improper surface preparation or application.	
NEO PAINTS FACTORY (PTY) LTD Reg No 2002/214		
12 Bell Street, Southern Industrial Area PO Box 5005 Windhoek, NAMIBIA Tel. +(264) 61-384 700 – Fax +(264) 61-233 914		Hanna Mupatani Road PO Box 762 Walvis Bay, NAMIBIA Tel. +(264) 64-204 026 – Fax +(264) 64-204 010