

## IMPORTANT THINGS TO KNOW



## OUR PRODUCT RANGE - ROOF PAINTS

## HOW TO PAINT A GALVANIZED METAL ROOF



Always follow the instructions on the product label for best results.



Preparation and correct product application are important.



There are no short-cuts. Always follow the correct drying time recommendations.

### HANDY PAINTING TIPS



Clean your equipment used for roof paint with soapy water after use.



Use a paint roller with a long handle to reach patches far away from you.



Paint your roof during mild temperatures of the day. Do not paint your roof if rain is expected.



Use correct safety equipment for your own protection e.g. safety glasses, gloves and protective clothing. Sunglasses is recommended.



Work from an extension ladder instead of going on the roof if possible. It's usually safer to work from a ladder instead of on the roof.



Wear a harness with a safety rope if possible.

PRODUCT NAME		SPECIALITY PRODUCTS			
		NEO ROOF PAINT	NEO HEAT REFLECTIVE ROOF	NEO CORROTEC	NEO CORROGUARD
APPLICATION AREAS	INTERIOR			X	X
	EXTERIOR	X	X	X	X
PROPERTIES	UV RESISTANT	X	X		
	HEAT REFLECTIVE		X		
	WATER RESISTANT	X	X		
SURFACES	CEMENT TILES	X	X		
	FIBRE CEMENT SHEETING	X	X		
	PLASTER	X	X		
	PREVIOUSLY PAINTED SURFACE	X	X		
	MILD STEEL	PRIMED	PRIMED	SAND BLASTED	SAND BLASTED
	GALVANIZED METAL	X	X	X	X
	ALLUMINIUM	PRIMED	PRIMED	X	X
	COPPER/BRASS	PRIMED	PRIMED	X	
	WOODEN SUBSTRATES	PRIMED	PRIMED		

Technical helpline: Tel: +264 61 384 724

**WINDHOEK HEAD OFFICE**  
12 Bell Street, Southern Industry, Windhoek  
T: +264 61 384 700

**WALVIS BAY REGIONAL OFFICE**  
Hanna Mupatani Road, Walvis Bay  
T: +264 64 204 026

[www.neopaints.com](http://www.neopaints.com) [f/NEOpaintsNamibia](https://www.facebook.com/NEOpaintsNamibia)

**PA!NTNAM!B!A**

## HANDY TIPS ON HOW TO PAINT A GALVANISED METAL ROOF AND WHICH PRODUCTS TO USE







Painting the roof of your home can improve the look and increase the value. A well cared-for roof is as easy as following the steps:

*A coat of excellence*



1


Use a paint scraper or a putty knife to scrape away loose paint on previously painted metal roofs.

Press the scraper or knife firmly against the paint, but make sure you don't damage the metal underneath.

Don't worry about patches where the paint is in good shape, as you can simply paint over those.

THINGS YOU WILL NEED

Hamilton's Stainless Steel Scraper 50mm



3

Remove all rust by sanding back the area to the bare metal.

Spot paint bare metal areas with **NEO Corrotect Primer** or **NEO Corroguard Primer** recommended for galvanized metal surfaces.

THINGS YOU WILL NEED

Hamilton's Perfection Ensign Brush




2

Ensure that the metal is clean and free from dust, oil, chemicals etc.

Clean the metal with **NEO Metal Conditioner** to remove the oil and grease.

Brush the metal with a stiff nylon brush and rinse after 15 minutes with clean tap water.

THINGS YOU WILL NEED



Nylon brush



4

Check for loose roofing nails, and seal all flashing and nails with **NEO Elastic Waterproofing**.

Apply using a brush.

THINGS YOU WILL NEED



Hamilton's Viva 75mm brush



5

Apply 2-3 coats of **NEO Roof Paint** or **NEO Heat Reflective Roof** by means of a brush, roller or spray.

Thickness of the layers is essential for the performance of the roof paint and to ensure adequate UV Resistance.

NOTE: Only paint if the temperature of the roof is between 10-30 degrees.

THINGS YOU WILL NEED



Paint tray 225mm



Hamilton's Specialist Roof Renovator



*finish*



MORE HANDY TOOLS



Wire brush



Scraper



Paint Tray



Sand paper



Paint roller



Paint brush